



P.O. Box 5
Raleigh, NC 27602
(919) 854-1844

TIME STAMPING METHOD EMPLOYING USER SPECIFIED TIME

BACKGROUND OF THE INVENTION

The present invention relates generally to cryptographic protocols and, more particularly, to a time-stamping protocol for time-stamping digital documents.

There are times when it is desirable to prove the existence of a document as of a particular date. For example, patent disputes concerning the inventorship of an invention often turn on who is able to produce corroborating documentary evidence dating their conception of the invention. A common procedure for dating records is to keep the records in a daily journal or notebook with each page sequentially numbered and dated. Another procedure for dating a record is to have the record witnessed by an uninterested or trusted party that can attest to the existence of the document. The increasing use of computers, however, makes these time-stamping methods obsolete. It is relatively easy to change the date-stamp added to a document by the computer when the document was created. Further, while it is difficult to alter a paper document without leaving some signs of tampering, digital records can be easily altered or revised without leaving any evidence of tampering. Therefore, people are less likely to trust a digital document than a paper document that has been time-stamped using conventional time-stamping procedures.

To be trusted, a time-stamping procedure for digital documents should meet the following criteria:

1. The data itself must be time-stamped, without any regard to the physical medium on which it resides.
2. It must be impossible to change a single bit of the data without that change being apparent.
3. It must be impossible to timestamp a document with a date and time different than the current date and time.

One method for time-stamping a digital document would be to archive the document with a trusted escrow agent. In this case, the document originator sends a copy of the digital document to a trusted escrow agent. The escrow agent records the date and time that the document was received and retains a copy in his archives. Later, if a dispute arises over the date of the document, the document originator can contact the escrow agent who produces his copy of the document and verifies that it was received on a particular date. This time-stamping procedure has a number of drawbacks. First, the document originator must disclose the contents of the document to the escrow agent. Also, large documents take a relatively long period of time to transmit to the escrow agent and they require a large amount of data storage.

An improvement of the escrow procedure is to use a hash of the document. Instead of sending the document to the escrow agent, the document originator hashes the document using a one-way hash algorithm and sends the generated hash value to the escrow agent. The escrow agent stores the hash value along with the date and time that it was received in his archives. Later the document originator can use the services of the escrow agent to prove the

existence of the document as of a particular date. The disputed document can be hashed and the resulting hash value can be compared to the hash value stored by the escrow agent in his archives for equality. If the hash values are equal, the document is presumed to be in existence as of the date associated with the stored hash value. One advantage of this method is that the document originator does not need to disclose the contents of the document to the escrow agent.

The need to escrow the document or hash value can be eliminated by having a time stamping authority generate a certified time stamp receipt using a cryptographic signature scheme as taught in U.S. Pat. No. Re. 34,954 to Haber et al. and Fischer, U.S. Patent No. 5,001,752. In this case, the document originator hashes the document and transmits the hash value to the time stamping authority. The time stamping authority appends the current date and time to the hash value to create a time stamp receipt and digitally signs the time stamp receipt with a private signature key. The time stamping authority's public verification key is distributed and available to anyone interested in validating a time stamp receipt created by time stamping authority. The public verification key is typically stored in a public key certificate signed by a Certification Authority so that anyone desiring to validate the time stamp receipt with the public key can have confidence in the authenticity of the key.

SUMMARY OF THE INVENTION

The present invention is a time-stamping protocol for time-stamping digital documents so that the date of the document can be verified. The method presumes the existence of a trusted agent referred to herein as the time-stamping authority (TSA). According to the present invention, the document originator creates a time stamp receipt by combining the document or other identifying data that can later serve as evidence of the substance of a document with a time indication. The document originator sends the time stamp receipt to a time stamping authority TSA. The TSA validates the time stamp receipt by comparing the time value specified in the submitted time stamp receipt with the current time derived from a trusted clock available to the TSA. If the time value specified in the time stamp receipt meets the time criteria established by the time stamping authority, the time stamping authority binds together the time value and document or other identifying data, e.g., by certifying the time stamp receipt R using a cryptographic signature scheme. For example, the time stamping authority may perform the binding operation (e.g., by certifying the time stamp receipt) where the date specified by the time stamp receipt equals the current date, or may perform the binding operation only on those records received within a predetermined time window.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates an illustrative embodiment of the time stamping method of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 is a flow diagram illustrating the general process of time-stamping a document according to the present invention. A document D is created at step 100. The document D is presumed to be in digital form and may comprise any alphanumeric, audio, or graphic presentation of any length. The document D may optionally be hashed at step 102 using a one-way hashing function. A hash function is a function that takes a variable length input string, called a pre-image, and converts it to a fixed-length string, called a hash value, denoted H. The pre-image in this case is the document D or selected portions thereof. A one-way hash function operates in only one direction. While, it is easy to compute a hash value from the pre-image, it is computationally impractical to find a pre-image that hashes to a given hash value. Thus, it is practically impossible to recover the pre-image given the hash value and knowledge of the hash algorithm. Another feature of a hashing function is that it is difficult to find any two pre-images that hash to the same value.

There are several advantages to sending a hash value H produced on document D instead of the document D itself. First, the hash value H improves security by functioning as a fingerprint of the document D. Changing a single bit in the document D will result in an entirely different hash value making it easy to detect efforts to modify a document D or hash value H. Second, the hash value H greatly reduces the amount of data that must be transmitted to the TSA. This factor can be important where the available bandwidth is limited. Third, by

sending a hash value H in place of the document D, the content of the document D does not need to be disclosed to the TSA.

Any known hashing function, such as the SHA-1, MD5, and RIPEMD-160, can be used in the present invention. For the remaining description of the time stamping protocol, it will be assumed that the document D has been hashed and that the hash value H has been sent to the TSA in lieu of the document D. It is understood, however, that one can practice the invention by substituting D, selected portions of document D, or some other function of D in place of the hash value H in the protocol.

The document originator generates a time stamp receipt R at step 104 by concatenating or otherwise combining identifying data associated with the document D with a time indication. The identifying data may be any digital data derived from or associated with the document D that can be used to identify the document D and may include a digital representation of the document D or selected portions thereof, or a digital sequence derived by application of some function (e.g. hash function) to the document D. In the disclosed embodiment, the identifying data comprises the hash value H generated on document D. Other optional data, such as the originator's identification number ID or a sequential record number SN, could also be used to generate the time stamp receipt R. The optional data could be provided by the document originator or by another party, such as the TSA. The time stamp receipt R is generated, for example, by concatenating the hash value H generated on document D with the current time T and optionally other data, such as the originator's ID number

and/or a sequential record number SN. The time stamp receipt R would, in this example, comprise the string (H, T, ID, SN).

After creating the time stamp receipt R, the document originator transmits the time stamp receipt R and other optional data to a time stamping authority TSA at step 106. After receiving the time stamp receipt R, the TSA verifies the time stamp receipt R at step 108. First, the TSA verifies that the data in the time stamp receipt R is consistent with data maintained and controlled by the TSA. For example, the TSA may require, as part of its time stamping services, that the document originator provide its ID number and a sequential record number SN. In this case, the TSA would verify that the data submitted by the document originator is consistent with data maintained by the TSA. If, for example, the sequential record number SN was out of sequence, the TSA may refuse to perform the binding operation as described below.

If the data in the submitted time stamp receipt R is consistent with data maintained by the TSA, the TSA then verifies the time value T specified in the time stamp receipt R. The time value T in the time stamp receipt R is compared against the current time T_{TSA} obtained from a trusted clock maintained by the TSA. Alternatively, the current time T_{TSA} can be obtained by the TSA from a trusted source. To be valid, the time value T specified in the time stamp receipt must be within a certain specified range of the current date and time established by the TSA. For example, the TSA may accept only those time stamp receipts where the specified date of the time stamp receipt R is equal to the current date. Alternatively, the TSA may specify a time window ΔT and accept only those time

stamp receipts submitted to the TSA (e.g., for certification) that fall within the specified time window ΔT from the current time T_{TSA} . The TSA performs the binding operation (e.g., by certifying time stamp receipts) only on those time stamp receipts that meet the time criteria established by the TSA. Time stamp receipts submitted to the TSA that do not meet this time criteria are rejected.

If the time stamp receipt R submitted by the document originator is determined to be valid at step 110, the TSA performs the binding operation at step 112 to cryptographically bind the identifying data, such as the hash value H , and time value T contained in the time stamp receipt R . One method for cryptographically binding the identifying data with the time value T is to sign the time stamp receipt with a private signature generation key K_{PR} to generate a certified time stamp receipt, denoted $\text{sig}(R)$. The signature generation key K_{PR} is part of a public and private key pair (K_P, K_{PR}) used by the TSA to certify time stamp receipts. The private key K_{PR} is known only to the TSA. The public key K_P is made available to the public so that anyone can verify or authenticate the TSA's signature. The public key K_P can be stored in a certificate signed by a Certification Authority CA so that the TSA's public key can be validated and, hence, trusted by those using the public key K_P . The time stamp receipt R can be signed using any known cryptographic signature scheme, such as a digital cryptographic signature scheme based on the RSA Algorithm.

Those skilled in the art will appreciate that there are numerous other ways to perform the binding operation. Signing the time stamp receipt R with a signature generation key belonging to the TSA is just one way of binding the time

value T and identifying data. The binding operation could also be accomplished by computing a Message Authentication Code (MAC) on the time stamp receipt R (or selected portions of R) using a secret key K belonging to the TSA. One method for binding a time value T with a document D using a Message Authentication Code is described in a separate application file simultaneously with this application entitled 'Time Stamping Method Employing Separate Ticket and Stub,' which is incorporated herein by reference. The binding operation might also be accomplished by encrypting the time stamp receipt R or selected portions of R using a cryptographic key belonging to the TSA. Another way to perform the binding operation is to compute a hash value on the time receipt R or selected portions of R . These examples are not intended to be exhaustive, but are intended to illustrate some of the techniques that could be used to perform the binding operation. All that is required is that the binding operation establish a verifiable link between the time value T and the document D or some function of the document D .

The binding operation produces binding information, denoted B_{INFO} , which is transmitted to the originator at step 114. If the binding operation is performed by signing the time stamp receipt R , then the binding information B_{INFO} consists of a digital signature generated on the time stamp receipt, denoted $sig(R)$. If the binding operation comprises generation of the Message Authentication Code, encrypted value, hash value, or some other function, then the binding information B_{INFO} would comprise the Message Authentication Code, encrypted value, hash

signing time stamp receipts) and transmitting binding information (e.g. signed time stamp receipts) to users. It would also be possible to implement some or all of the steps in firmware, or in hard-wired logic.

The present invention may, of course, be carried out in other specific ways than those herein set forth without departing from the spirit and essential characteristics of the invention. The present embodiments are, therefore, to be considered in all respects as illustrative and not restrictive, and all changes coming within the meaning and equivalency range of the appended claims are intended to be embraced therein.